



effect glass S.A.
ul. Hauke Bosaka 2
25-214 Kielce
Poland

effect glass S.A.
Wędkowy Branch
83-115 Swarzędz
Poland

according to requirements of the standard:

PN-EN 1279-5+A2:2011 Schedule ZA

name / intended use of the product:

insulated glass unit / for use in construction industry and construction works

identification of the product:

4AS/16/4GLE+A (ANTISOL SZARY)

Characteristics:

Characteristics:	Value:	Standard
Fire resistance	NPD	EN-13501-2
Reaction to fire	NPD	EN-13501-1
Behavior of external fire	NPD	
Bullet resistance	NPD	EN 1063
Explosion resistance	NPD	EN 13541
Resistance against manual attack	NPD	EN 356
Pendulum body impact resistance	NPD	EN 12600
Resistance against sudden temperature changes and temperature differentials	[°K] 40/40	EN 572
Wind, snow, permanent and imposed load resistance	[mm] 4/4	
Airborne sound insulation	$R_w(C;C_{tr})$ [dB] NPD	EN 12758
Light transmittance factor	τ_v [%] 49	EN 410
Light reflectance factor	ρ_v / ρ'_v [%] 9/15	EN 410
Solar direct transmittance factor	τ_c [%] 33	EN 410
Solar direct reflectance factor	ρ_e / ρ'_e [%] 19/NPD	EN 410
Total solar energy transmittance factor	g [%] 39	EN 410
Thermal transmittance factor	U [W/m ² K] 1,0	EN 673

NPD - No performance determined

Effect Glass S.A. declares, under its sole responsibility, that the construction product is in conformity with the above performance characteristics.

Technical Director

W. Bratek

Waldemar Bratek

Kielce, 2016-08-30

Notified Body taking part in conformity assessment of the product:

Institute of Ceramics and Building Materials in Warsaw. Glass and Building Materials Division in Cracow. Glass Technology Unit. 30-702 Cracow ul. Lipcowa 3 - Initial Type Testing

Institute of Ceramics and Building Materials in Warsaw. Ceramics and Glass Section. 02-676 Warsaw ul. Postępu 9 - Factory Production Control Certificate, Conformity Certificate acc. To. PN-EN 1279-5

Schedule no. 1 to the Declaration of Performance:

Copy of particulars accompanying CE marking